

TECHICAL DATA SHEET

TECHNICAL CHARACTERISTICS

LEVELMAX Primer X is a low VOC, water based acrylic primer with a magenta tint. As a one component primer, it is designed for diverse substrates. It is designed to enhance the performance of self levelling underlayments on both porous and nonporous surfaces. The single coat application allows for quick, cost efficient work, and it features easy handling and application.



WHERE TO USE

- Ideal for priming interior surfaces.
- Highly recommended to be used as a primer prior to the application of cementitious self levelling underlayments, such as LEVELMAX ProFlow.
- Applicable before putty application.
- Applicable on masonry substrates, ALC wall panels, concrete, plaster layers, and brick and concrete walls.

RECOMMENDATIONS

- Application temperature range is from +5 degrees Celsius to +35 degrees Celsius (this is a recommendation, not a strict prohibition).
- Store at temperatures above 0 degrees Celsius.

APPLICATION PROCEDURE

- Preparing the substrate: Remove any loose dust, oil stains, release agents, and loose layers from the base surface to make it clean, stable, and free of dust or grease. For areas with loosened or cracked surfaces, they must be chiselled out and repaired in advance. If the base material has high water absorption, it should be thoroughly wetted with clean water beforehand.
- Application: It is recommended to use a roller or brush to apply the primer evenly in a crisscross pattern, making a continuous and complete coating for optimal surface preparation. Apply the primer with a thickness of approximately 0.5 mm in a single coat. After application, allow the primer to air dry naturally for full curing, before the highly recommended application of LEVELMAX ProFlow.
- Cleaning: Clean all tools and application equipment immediately after use. Once cured, residual material can only be removed mechanically.

PACKAGING

LEVELMAX Primer X is supplied in a 20 kg bucket.

STORAGE

12 months when stored in the original unopened packaging in a dry, elevated area. Keep the containers in a dry, cool, well ventilated space, away from sources of heat and ignition. Containers must be kept tightly closed and handled with care.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Avoid contact with skin and splash into the eyes, and wear good safety gloves. If swallowed, drink 1 or 2 glasses of water to dilute the substance and avoid inducing vomiting. Seek immediate medical attention or contact a poison control centre.



TECHNICAL DATASHEET

Property	Value
Consistency	Liquid
Colour	Milky white
Dry solids content (%)	14% to 20%
VOC	0 g/l
Application Data (at +23 degrees Celsius, 50% R.H.)	
Thickness Per Coat	0.5 mm
pH	6.5 to 8.5
Application Temperature Range	from +5 degrees Celsius to +35 degrees Celsius
Pot Life	8 hours
Drying time before the application of levelling compounds	1 to 2 hours (depending on weather conditions)

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. Please refer to the current version of the Technical Data Sheet, available from our website www.levelmax.com.au.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the LEVELMAX product installation. The most up to date TDS can be downloaded from our website www.levelmax.com.au. ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF LEVELMAX AUSTRALIA.